

KUB

IMF8-1W50-125H(311)

Application

The low-power KUB projector is specifically designed for accent lighting of facade elements. Its compact size makes it ideal for installation on columns, canopies, narrow inter-window spaces, or decorative details.





Light color	White 5000 K
CRI	> 80
Color binning	2 MacAdam steps
Optics, degrees	125
Delivered lumens, lm	600
Voltage, V	230 AC 50 Hz
Wattage, W	10
Power factor	> 0,9
Electric class	I (first)
Protection class	IP66
Operating temperature, degrees C	-40 ... +55
IK rating	IK08
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	104x170x110
Weight, kg	1,3
Content of delivery	luminaire, package, passport, mounting instructions

Standard RAL colors

1015	1001	8004	8017
9005	7016	9006	9003

Standard coating type
moire



Mounting

Surface mounted, on a swivel bracket.

Materials

Housing, bracket — aluminum casting alloy, covered with powder paint; protective glass — silicate tempered glass; metalware — stainless steel.

Integrated technologies

ColorPro® technology is a software algorithm that optimizes the use of the luminaire's available power to deliver peak brightness.

EternalTechnology® is a continuous monitoring of the internal temperature of the lighting fixture through the system of integrated sensors.

Truelight® technology - a comprehensive suite of solutions designed to deliver flawless lighting effects.

Aquatech® technology – a multi-stage protection technology safeguards luminaires against water ingress.

COOLight® technology is aimed at increasing the efficiency of lighting fixtures.

Additional codes definition

(111) - Version with inner accessory, type 1 (for medium and narrow optics), cable length - 1 m;

(H111) - Version with inner accessory (hexagonal lattice), cable length - 1 m;

(211) - Version with inner accessory, type 2 (for wide optics), cable length - 1 m;

(311) - Version with inner accessory, type 3 (for wide optics), cable length - 1 m;

(011) - Version without inner accessory, cable length - 1 m.

Accessories

brackets

KUB-03-75 - for the pole, static

KUB-01-110 - for the pole, swivel (1 hole)

KUB-02-110 - for the pole, swivel (2 holes)

louvres

KUB-02-050 - 50 mm height

KUB-02-075 - 75 mm height

tubes

KUB-01-075 - 75 mm height

spikes

KUB-01-400-55 - into the ground, 400 mm depth, luminaire 55 mm above the surface

KUB-02-400-150 - into the ground, 400 mm depth, luminaire 150 mm above the surface

Compatible control system devices