

PILL

IRF1-3W40-30H

Application

A compact lighting fixture designed for facade and landscape accent illumination. It features a versatile range of secondary optics, including an ultra-narrow 5° option, making it highly practical for applications such as grazing and flood lighting.



Light color	White 4000 K
CRI	> 80
Color binning	2 MacAdam steps
Optics, degrees	30
Delivered lumens, lm	200
Voltage, V	230 AC 50 Hz
Wattage, W	3
Power factor	> 0,9
Electric class	I (first)
Protection class	IP66
Operating temperature, degrees C	-40 ... +55
IK rating	IK09
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	48x54x111
Weight, kg	0,3
Content of delivery	Luminaire, package, passport, mounting instructions

Mounting

Surface mounted

Materials

Housing — aluminum alloy with galvanic coating, covered with powder paint; protective glass — shock-resistant polycarbonate; bracket — stainless steel; metalware — stainless steel.


Integrated technologies

None

Standard RAL colors

1015	1001	8004	8017
9005	7016	9006	9003

Standard coating type
moire



Additional codes definition

Accessories

Customized accessories are manufactured according to the project

Compatible control system devices